

Technical Data Sheet



Acryset

Cold Applied Durable Fast Dry Waterborne



Characteristics:

- ❖ Low VOC
- ❖ Excellent glass bead retention and night visibility
- ❖ Dry through in 2 hours maximum even at high humidity
- ❖ Non-flammable
- ❖ Non-bleeding
- ❖ Spreading rate of 300 linear feet per gallon of 4-inch line
- ❖ Easy clean-up with soap and water
- ❖ Recommended for sealcoated surfaces
- ❖ 100% Acrylic Binder

Cautions:

- ❖ **CANNOT** be used in galvanized, brass, aluminum, or steel equipment; Recommend stainless steel or plastic components
- ❖ Keep from freezing
- ❖ Addition of water or other soluble solvents will adversely affect dry time
- ❖ All equipment should be cleaned before paint dries

Specifications

Viscosity:	85 – 95 Krebs Units	Total Solids:	72 % Minimum
Weight per Gallon:	13.50 Minimum	Dry to NPU:	3 to 10 Minutes track free at 15 mils wet
Shelf Life:	1 Year Minimum Properly Stored	Vehicle Type:	100% Acrylic fast release resin
Water Resistance:	2 hours minimum drying at temperatures above 50°F and humidity below 80% before exposure to moisture		