

Technical Data Sheet



Plastibar Thermoplastic Paint



Characteristics:

- ❖ Up to 5 times the life of regular traffic paint
- ❖ Excellent proven substitute for hot and pre-formed thermoplastic
- ❖ Hard semi-gloss finish, stays cleaner longer
- ❖ Outstanding durability
- ❖ Spreading rate of 300 linear feet per gallon of 4-inch line
- ❖ Can be applied with standard striping equipment, without modification
- ❖ Particularly recommended for high wear traffic areas, such as intersections, crosswalks, legends, factories, parking decks, and warehouses
- ❖ Excellent hiding and brightness
- ❖ Superior bead adhesion for high night visibility
- ❖ Easy clean-up with Xylene or Toluene

Cautions:

- ❖ May bleed on fresh asphalt or sealcoated surfaces – See “Application Procedures – Solvent Based Paint”
- ❖ This paint may lift improperly aged or inferior asphalt pavements
- ❖ Keep away from all heat sources – **FLAMMABLE**

Specifications

Viscosity: 80 – 90 Krebs Units	Total Solids: 68 % Minimum
Weight per Gallon: 11.50 Minimum	Solvent Type: Toluene
Shelf Life: 1 Year Minimum Properly Stored	Vehicle Type: Thermoplastic Polymer
Dry to NPU: 2 to 10 Minutes track free at 15 mils wet	